

LOW RESISTANCE TO AIR FLOW

MOISTURE RESISTANT 100% SYNTHETIC MEDIA

SUPPORTS ACHIEVEMENT OF LEED CREDITS

UL CLASS 2 RATED

STANDARD AND CUSTOM SIZES



INITIAL RESISTANCE (W.G.) AT 500 FPM

FILTER DEPTH	MERV 11		MERV 13		MERV 14		FINAL RESISTANCE
	6 pkt	8 pkt	6 pkt	8 pkt	6 pkt	8 pkt	
12"	0.52	0.46	0.69	0.61	0.98	0.83	1
15"	0.5	0.45	0.6	0.49	0.76	0.63	1
22"	0.39	0.35	0.43	0.41	0.53	0.47	1
29"	0.38	0.34	0.41	0.36	0.46	0.38	1
36"	0.45	0.36			0.5	0.41	1

PRODUCT DATA INFO - MERV11/13/14

NOMINAL SIZE	ACTUAL SIZE	TOTAL POCKETS	MEDIA AREA (sq. ft)
24X24X12	23 3/8 x 23 3/8 x 12	6 pocket	30 sq.ft
24X24X15	23 3/8 x 23 3/8 x 15	6 pocket	33 sq.ft
24X24X15	23 3/8 x 23 3/8 x 15	8 pocket	42 sq.ft
24X24X22	23 3/8 x 23 3/8 x 22	6 pocket	48 sq.ft
24X24X22	23 3/8 x 23 3/8 x 22	8 pocket	62 sq.ft
24X24X22	23 3/8 x 23 3/8 x 22	10 pocket	76 sq.ft
24X24X29	23 3/8 x 23 3/8 x 29	6 pocket	66 sq.ft
24X24X30	23 3/8 x 23 3/8 x 29	8 pocket	84 sq.ft
24X24X30	23 3/8 x 23 3/8 x 29	10 pocket	103 sq.ft
24X24X36	23 3/8 x 23 3/8 x 36	6 pocket	84 sq.ft
24X24X36	23 3/8 x 23 3/8 x 36	8 pocket	102 sq.ft
24X24X36	23 3/8 x 23 3/8 x 36	10 pocket	124 sq.ft